AHAR PowerStation Services

Product Data Sheet

RAMONA Analog Output module

Model: AAI2543-S50

Description

I/O modules are building blocks of industrial control systems used in end equipment such as PLC (Programmable Logic Controllers), PAC (Programmable Automation Controller) and DCS (Distributed Control Systems). Analog input/output modules capture and measure signals such as temperature, pressure, flow, level, vibration and motion. These parameters are transmitted from equipment such as sensors and other field devices on the factory floor in the form of current or voltage. Current-loops typically range from 4-20mA.

Functionality

These modules provide 16 outputs of 4 – 20 mA signal. They can be used in dual-redundant configuration.

Key Feature

- 16, isolated output channels
- output signal is 4 to 20 mA
- Accuracy is ±48µA
- Data update period is 10ms
- Drift due to ambient temperature change is ±16 µA/10 ˚C

© Copyright AHAR AG2022

Specification

Number of output channels	16, isolated
output signal	output signal 4 to 20 mA
Withstanding voltage	Between input and system: 1500 V AC, for 1 minute
Accuracy	±48 µA
Data update period	10 ms
Allowable load resistance	0 to 750 Ω
Circuit-open detection	Less than 0.65 mA
Drift due to ambient temperature change	±16 µA/10 ˚C
Maximum current consumption	230 mA (5 V DC), 540 mA (24 V DC)

Mechanical

Connection technology	Pressure clamp terminal, MIL connector cable, dedicated cable (KS1)
Dimension	
• Width	32.8 mm
• Height	130 mm
• Depth	107.5 mm
weight	310 gr
Installation	Snaps onto Backplane (ANB2010D)
Electrical accessories	MIL Connector Cable
IP degree of protection	IP30

© Copyright AHAR AG2022